

A6

The full electric tracked apron feeder A6 functions as a buffer with its 8m³ hopper and makes sure the following machine, often a stacker, is evenly fed with material.

The hopper can be turned 90°, so hopper can be aligned with tracks or in 90° position

Apron feeder can be lifted hydraulically from transport to operation position (20-25°)

35
kWh

Electric plug-in
mains

Applications

Buffer
Load

- The full electric tracked apron feeder A6 functions as a buffer with its 8m³ hopper and makes sure the following machine, often a stacker, is evenly fed with material.
- Can power several e-driven machines separately or in line
- Standard 450L tank

| TECHNICAL SPECIFICATIONS | |
|---|---|
| Capacity up to | 660 sT |
| Weight | 15 sT |
| Hopper | 10 yard³ |
| Feed hopper in HB450 | • |
| Hydraulic foldable hopper walls | • |
| Loading height | 11'8" |
| | Loading width (back) 10'2" |
| | Side loading length 14'5" |
| | Wear lining • |
| Heavy Duty Plate Apron Feeder | 11'8" x 4'3" |
| Swiveling hopper by 90°, hopper can be in line with tracks or in 90° position | • |
| Track-unit: Length, total width, track shoe width | 10'11", 8'2", 1'4" |
| 2-speed track drive | 0,7 / 1,2 mph |
| Engine unit(s) | Electric plug-in |
| Control | PLC – IP 67 LCD screen 4,3" & remote control |
| Available drive systems | |
| | Diesel/hydraulic drive / |
| | e-drive Diesel/hybrid, electric plug-in & plug-out / |
| | ZERO drive (no combustion engine, plug-in electric) • |

OPTIONS

| | |
|---------------------------------------|---|
| Wear lining in HB450/500 | • |
| Hopper extensions up to 19,6 yard² | • |
| Increased feeding chute | • |
| Radio remote | • |
| Volumetric belt scale on apron feeder | • |

| TRANSPORT | |
|---------------------|----------------------|
| Transport l x w x h | 16'5" x 8'4" x 10'3" |

| LEGENDA | |
|---------|-------------------------------|
| • | applicable - available |
| / | not applicable- not available |

