

Can power several electric machines and other electric appliances

besides the machine, or on the tracked platform

• Standard 450L tank



TECHNICAL SPECIFICATIONS	
Capacity up to	352 kW, 450 kVA
Weight	12 sT
Drop Off - Drop On module, can be placed on top of e-drive crushers,	•
besides the machine or on the tracked platform	
Standard 450 l / 118 gal fuel tank	•
Track-unit: Length, total width, track shoe width	10'10", 8'2", 1'4"
2-speed track drive	0,7/1,2 mph
Engine unit(s)	352 kW, 450 kVA
"Power plug out:	
POWER LOCK plug-out 3 Phases, 400V;	
50 Hz; 450 kVA (660 A)	•
Plug out 3 Phases, 400V; 50 Hz, 32 A	
Plug-out 3 Phases, 400V; 50 Hz, 63 A"	
Control	PLC – IP 67 LCD screen 4,3" & remote control
Available drive systems	
Diesel/hydraulic drive	•
e-drive Diesel/hybrid, electric plug-in & plug-out	electric plug out
ZERO drive (no combustion engine, plug-in electric)	electric plug out

OPTIONS

Additional 2000 l fuel tank placed on platform for more autonomy	•
Radio remote	•
Working lights	•
Plug-in connections, 3 phases+ E, 660 A Powerlock & 25 m cable	•

TRANSPORT	
Transport l x w x h	20'8 x 8'2" x 8'8"

LEGENDA	
•	applicable - available
/	not applicable- not available





