

The P3 tracked shredder is a compact and highly efficient two-shaft shredder which can be used in numerous applications from waste wood processing to construction waste.



5,3  
US Gal/h

Diesel-hydraulic

### Applications

Construction waste  
Mineral waste  
Biomass  
Green waste  
Stem wood and roots  
Waste wood  
Industrial & household waste  
Plastics  
Light metal scrap  
Tires  
And others

Heavy duty full metal shafts which are easy to replace

- Easy service and maintenance access
- More torque

TECHNICAL SPECIFICATIONS	
Capacity up to	11- 110 sT
Weight	17,6 sT
Feed opening (l x w)	5'3" x 3'11"
Tiltable loading platform 45°	•
Hopper in ST 520 steel	3 yard³
Loading height	8'3"
	Loading width (back) 7'3"
	Side loading length 13'5"
Twin shaft shredder	•
Feed opening (l x w)	5'3" x 3'11"
Shaft diameter	2'4"
Driving torque	90000 Nm per shaft = 180000 Nm
Speed of shaft (shafts change direction of rotation according to program)	45 & 25 RPM
Automatic release system by reversing shafts	•
Several grids available	•
Several sets of shafts available depending on application	•
Time for changing shafts and grid	approx. 1 hour
Main conveyor belt (l x w) & (discharge height)	23' x 2'7" (12'3")
Main conveyor hydraulic foldable for transport	•
Maintenance free tail drum	•
Track-unit: Length, total width, track shoe width	7', 7'3", 1'4"
speed track drive	1,5 mph
Engine unit(s)	170 kW
Control	PLC – IP 67 LCD screen 4,3" & remote control
Available drive systems	
	Diesel/hydraulic drive •
	e-drive Diesel/hybrid, electric plug-in & plug-out /
	ZERO drive (no combustion engine, plug-in electric) /

## OPTIONS

Wear lining in HB450	•
Radio remote	•
Magnetic separator	•
Working lights	•
Built on after screen 50 mm and discharge conveyor fines	•
Fuel filling pump	•

TRANSPORT	
Transport l x w x h	25'3 x 7'3" x 8'3"

LEGENDA	
•	applicable - available
/	not applicable- not available

